



GSLX Series Right Angle Modular Jack with LED, Tab Down

Features 

- Easy Viewing LEDs to Act as Power/Transmit Indicators
- Snap in Retention Tabs
- Available Fully Shielded for EMI/RFI Protection
- CSA/NRTL Certified File No. LR78160

Performance Specifications

Materials and Finish

Housing Material

PBT Thermoplastic, UL 94V-0 Rated

Contact Material

Phosphor Bronze

Plating

Gold Plated over Nickel in Contact Area Tin in Solder Area

Shield Material

Brass, Nickel Plated

Electrical Characteristics

Current Rating

1.5A

Voltage Rating

125V DC

MODULAR JACKS AND PLUGS

GSLX Series

Documentation & Ordering Information

Kycon Part #		

Part Number Builder

Series	Shield Option	Number of Positions & Contacts	Ground Pin Spacing	LED Color Option	Plating Option
Series GSLX - Right Angle Modular Jack PCB Mount	Shield Options N - Non-Shielded With 3.38mm LED Pin to Peg N2S - Shielded With 3.38mm LED Pin to Peg N1S2 - Shielded With Top Grounding Tabs 2.79mm LED Pin to Peg N2S2 - Shielded With Top Grounding Tabs 3.38mm LED Pin to Peg	Number of Positions/Contacts 88 - 8 Positions/ 8 Contacts	Ground Pin Spacing Blank (Non-shielded only) 3.05 mm - 3.05mm Ground Pin Spacing (Shielded only)	LED Color G/G - Green/Green G/Y - Green/Yellow Y/G - Yellow/Green	Plating Option Blank - Gold Flash (Standard) 50 - 50µ" Gold Plating

GSLX-N-88-x-x Series

Dimensions in mm

